



< Tuff Skin

TUFF SKIN

Technical Data

- Sturdy C9 and C-9M staggered-mount filament for rough/vibration service applications
- Silicone and Teflon coating is shatter-resistant and protects lamp from thermal shock
- Brass base

Benefits

- Available in A15, A19, A21, B10, BR30, BR40, PS25, R12, R20 and T10

Applications

- Food service
- Freezers/commercial coolers
- Outdoor lighting
- Drop lights
- Construction sites

ISO 9001 Certified

NATURALLIGHTING.COM

www.naturallighting.com

email: sales@naturallighting.com

Toll Free: 888.900.6830

Phone: 281.559.4900

FAX: 281.559.4949

Silicone and Teflon coating is shatter-resistant and protects lamp from thermal shock

Call Halco today and get a great look at our vast product line, personal service and fast delivery. Visit us at halcolighting.com.

Your account representative is your single source for pricing, orders, and technical support.

Shipping from Atlanta, Cleveland, Houston, and Phoenix.



*where there's light,
there's halco™*

(800) 677-3334

halcolighting.com

TUFF SKIN COATED - INCANDESCENT

Bulb Type	Watts	Base	Item #	Product Code	Description	Inner/Master	Volts	Filament Design	MOL
A-15	40	Med	6146	A15TF40	Silicone Coated	20/120	130	C-9	3-1/2"
A-15	60	Med	6147	A15TF60	Silicone Coated	20/120	130	C-9	3-1/2"
A-19	25	Med	101124	A19TF25	Silicone Coated	20/120	130	C-9	4-1/4"
A-19	40	Med	101125	A19TF40	Silicone Coated	20/120	130	C-9	4-1/4"
A-19	60	Med	6141	A19TF60	Silicone Coated	20/120	130	C-9	4-1/4"
A-19	75	Med	6142	A19TF75	Silicone Coated	20/120	130	C-9	4-1/4"
A-19	100	Med	6143	A19TF100	Silicone Coated	20/120	130	C-9	4-1/4"
A-21	100	Med	6041	A21TF100/P5	Silicone Coated	12/60	130	C-9M	5"
A-21	150	Med	6043	A21TF150/P5	Silicone Coated	1/60	130	C-9M	6-1/8"
B-10	40	Med	102148	ETC40/TF	Silicone Coated	25/500	130	CC-2V	3-7/8"
B-10	60	Med	102146	ETC60/TF	Silicone Coated	25/500	130	CC-2V	3-7/8"
BR-30	65	Med	404051	BR30TF65	Silicone Coated	1/24	130	C-9	5-3/8"
BR-40	120	Med	404065	BR40FL120/5/TEF	Silicone Coated	1/24	130	C-9	6-1/2"
BR-40	250	Med	404066	BR40CL250/1/TEF	Shatter Proof Heat	1/12	120	C-9	6-1/2"
PS-25	150	Med	401345	PS25TF150/P5	Silicone Coated	1/60	130	C-9M	6-15/16"
PS-25	200	Med	401347	PS25TF200/P5	Silicone Coated	1/60	130	C-9M	6-15/16"
R-12	20	SC Bay	1383/TF	1383/TF	Silicone Coated	10/1000	13	C-8	2-5/8"
R-20	50	Med	104016	R20TF50	Silicone Coated	10/100	130	C-9	3-7/8"
R-40	250	Med	404071	R40RED250/10/TEF	Coated Red Faced Heat	1/12	120	C-9	6-1/2"
T-10	40	Med	106228	T10TF40	Silicone Coated	25/200	130	C-5V	5-3/16"
R-40	375	Med	104050	R40CL375/TEF	Shatter Proof Heat	1/12	120	C-9	6-9/16"

NATURALLIGHTING.COM

www.naturallighting.com

email: sales@naturallighting.com

Toll Free: 888.900.6830

Phone: 281.559.4900

FAX: 281.559.4949